IPsec Add-on for PCF®

Version 1.6

User's Guide

© 2018 Pivotal Software, Inc.

Pivotal

Table of Contents

Table of Contents	2
IPsec Add-on for PCF	3
Installing the IPsec Add-on for PCF	4
Upgrading the IPsec Add-on for PCF	11
Uninstalling the IPsec Add-on for PCF	12
Checking Certificate Dates	13
Troubleshooting the IPsec Add-on for PCF	15
Rotating Active IPsec Certificates	21
Renewing Expired IPsec Certificates	23
Release Notes	25



IPsec Add-on for PCF

Page last updated:

This guide describes the IPsec Add-on for PCF, which secures data transmissions inside Pivotal Cloud Foundry (PCF). Topics covered in this guide include IPsec Add-on for PCF installation and configuration, troubleshooting, and certificate rotation.

Your organization may require IPsec if you transmit sensitive data.

Overview

The IPsec Add-on for PCF provides security to the network layer of the OSI model with a strongSwan 🗵 implementation of IPsec. The IPsec Add-on provides a strongSwan job to each BOSH-deployed virtual machine (VM).

IPsec encrypts IP data flow between hosts, between security gateways, and between security gateways and hosts. The IPsec Add-on for PCF secures network traffic within a Cloud Foundry deployment and provides internal system protection if a malicious actor breaches your firewall.

IPsec Implementation Details

The IPsec Add-on for PCF implements the following cryptographic suite:

Key Agreement (Diffie-Hellman)	IKEv2 Main Mode
Bulk Encryption	AES128GCM16
Hashing	SHA2 256
Integrity/Authentication Tag	128 bit GHASH ICV
Digital Signing	RSA 3072/4096
Peer Authentication Method	Public/Private Key

Refer to the following topics for more information about the IPsec add-on:

- Installing the IPsec Add-on for PCF
- Rotating IPsec Certificates
- Renewing Expired IPsec Certificates
- Troubleshooting the IPsec Add-on for PCF
- Upgrading the IPsec Add-on for PCF
- Uninstalling the IPsec Add-on for PCF
- Release Notes



Installing the IPsec Add-on for PCF

Page last updated:

This topic describes how to prepare your network for IPsec, create an IPsec manifest, and add IPsec to your deployment.

Prerequisites

To complete the IPsec installation, verify that you have satisfied the following prerequisites before you begin:

- Google Cloud Platform (GCP), vSphere, Azure, Amazon Web Services (AWS), or OpenStack as your laaS
- Pivotal Cloud Foundry (PCF) operator administration rights
- BOSH deployed through Ops Manager 1.7 or later
- Set the MTU for your laaS in the Elastic Runtime tile, under **Networking**. Pivotal recommends MTU values of 1354 on GCP, 1438 on Azure, and the default values on AWS and vSphere. For OpenStack, follow the recommendations of your Neutron/ML2 plugin provider, or empirically test the correct MTU for your environment.

Limitations

• The IPsec add-on v1.6 does not work on Windows.

Best Practices

- IPsec may affect the functionality of other service tiles. As a result, Pivotal recommends deploying Elastic Runtime and each service tile to different isolated subnets. Alternatively, you can minimally deploy all service tiles to a single isolated subnet, apart from the Elastic Runtime subnet. Some service tiles do not support IPsec and must be placed in a non-IPsec subnet.
- For IPsec, Pivotal recommends any Ubuntu stemcells for vSphere, OpenStack, and HVM stemcells for AWS. These stemcells are available on Pivotal Network . If you use PV stemcells obtained from bosh.io , see the Packet Loss section of the Troubleshooting the IPsec Add-on for PCF topic to adjust MTU values.

Configure Network Security

Refer to the appropriate section below for your IaaS network configuration details.

Google Cloud Platform

To configure your Google Cloud Platform (GCP) environment for IPsec, perform the following steps:

- 1. Navigate to the **Networking** section of the GCP Console.
- 2. Click Firewall rules.
- 3. Click Create Firewall Rule.
- 4. For **Name**, enter ipsec.
- 5. For **Network**, select the network where Ops Manager is deployed. For example, **opsmgr**.
- 6. For Source filter, select Allow from any source (0.0.0.0/0).
- 7. For Allowed protocols and ports, enter udp:500; ah; esp.
- 8. Click Create.
- 9. Adjust the MTU value to 1354 by performing the procedure in the Packet Loss section of the Troubleshooting the IPsec Add-on for PCF topic.

vSphere

Confirm that your network allows the protocols listed in the table below.

Protocol Name	Protocol Number	Port(s)
AH	51	Any
ESP	50	Any
UDP	17	500

Azure

1. Confirm that your network allows the protocols listed in the table below.

Protocol Name	Protocol Number	Port(s)
АН	51	Any
ESP	50	Any
UDP	17	500

2. Adjust the MTU value to 1438. For instructions, see Explanation: Packet Loss.

AWS

To configure your AWS environment for IPsec, perform the following steps:

- 1. Navigate to EC2 Dashboard > Security Groups.
- 2. Select the Security Group with the description PCF VMs Security Group and click Edit.
- 3. Create the following **Inbound Rules**.

Туре	Protocol Name	Protocol Number	Port Range	Source
Custom Protocol	AH	51	All	10.0.0.0/16
Custom Protocol	ESP	50	All	10.0.0.0/16
Custom UDP Rule	UDP	17	500	10.0.0.0/16

Note: The default PCF VMs Security Group is typically specified with a subnet of 10.0.0.0/16. If your PCF subnet is deployed to a different CIDR block, adjust the source as needed.

OpenStack

Note: The following network configuration is optimized for Mirantis OpenStack, but other OpenStack distributions have a similar workflow.

To configure your Mirantis OpenStack environment for IPsec, perform the following steps:

- 1. Navigate to Project / Access & Security.
- 2. Select the security group and click **Manage Rules**.
- 3. Create the following Ingress and Egress Rules. Adjust the source CIDR as needed for your environment.

Protocol Name	Protocol Number	Port Range	Source
ESP	50	Any	0.0.0.0/0
АН	51	Any	0.0.0.0/0



UDP 17 500 0.0.0.0/0

Create the IPsec Manifest

Follow these steps to create the IPsec manifest for your deployment:

1. Create an IPsec manifest file ipsec-addon.yml, starting with the code below as a template.

```
releases:
- {name: ipsec, version: 1.0.0}
addons:
- name: ipsec-addon
  jobs:
    name: ipsec
  include:
   stemcell:
         os: ubuntu-trusty
  properties:
    ipsec:
      optional: false
      ipsec subnets:
      - 10.0.1.1/20
      no_ipsec_subnets:
      - 10.0.1.10/32 # bosh director
      - 10.0.1.4/32 # ops manager
      instance_certificate: |
           ---BEGIN CERTIFICATE--
        MIIEMDCCAhigAwIBAgIRAIvrBY2TttU/LeRhO+V1t0YwDQYJKoZIhvcNAQELBQAw
          ---END CERTIFICATE---
       instance private key:
           --BEGIN EXAMPLE RSA PRIVATE KEY--
        EXAMPLEXRSAXPRIVATEXKEYXDATAXEXAMPLEXRSAXPRIVATEXKEYXDATA
        ----END EXAMPLE RSA PRIVATE KEY----
       {\tt ca\_certificates:}
          ----BEGIN CERTIFICATE----
          {\tt MIIFCTCCAvGgAwIBAgIBATANBgkqhkiG9w0BAQsFADAUMRIwEAYDVQQDEwl0ZXN0}
          ----END CERTIFICATE----
        - |
            ---BEGIN CERTIFICATE---
          {\tt MIIFCTCCAvGgAwIBAgIBATAAYDVQQDEwl0ZXN0NBgkqhkiG9w0BAQsFADAUMRIwE}
          ----END CERTIFICATE----
      prestart timeout: 30
       esp_proposals: aes128gcm16!
       ike_proposals: aes128-sha256-modp2048!
```

- 2. Replace the values listed in the template as follows:
 - o releases: version : Specify the version number of your IPsec download from Pivotal Network.
 - o jobs: name : Do not change the name of this job. It must be ipsec .
 - o include: stemcell os : Do not change the OS type. IPsec is only supported on ubuntu-trusty .
 - o optional: Makes IPsec enforcement optional. To add IPsec, set this flag to true. Once IPsec has been successfully installed, set this flag back to false and redeploy.
 - ipsec_subnets: List the subnets that you want to be encrypted. You can include the entire deployment or a portion of the network. Encrypt any network that handles business-sensitive data.
 - o no_ipsec_subnets: List the IP address of your BOSH Director and Ops Manager VM, along with any other IP addresses in your PCF deployment that you want to communicate without encryption. Pivotal recommends that you list the subnets that are used for PCF managed services.

 Subnets for PCF managed services that do not support IPsec must be listed under no-ipsec.
 - Note: In GCP, if you use the default router for DNS instead of the Google public DNS at 8.8.8.8, you must add the IP address of the default router in your subnet to no_ipsec_subnets. For example, 10.0.0.1/32.
 - o <u>instance_certificate</u>: Copy in the signed certificate that will be used by all your instance VMs. You must use one of the CAs in the ca_certificates property to sign this certificate. For a development or test environment, you can use a self-signed certificate. See the <u>Generate a Self-Signed Certificate</u> section of this topic for more information.
 - $\verb| instance_private_key|: Copy in the private key that corresponds to the instance_certificate above. This key must not use a pass phrase. \\$
 - ca_certificates : Copy in CA certificates for the instance VM to trust during the validation process. In most cases, you only need the CA



certificate used to sign the instance certificate. During CA certificate rotation, you need two CA certificates.

- prestart_timeout : You can modify the 30 second default prestart timeout value. This value limits the number of seconds allowed for IPsec to start before failing the attempt.
- esp_proposals: You can modify the ESP (Quick Mode) encryption and integrity algorithms. The default, aes128gcm16!, is 128 bit AES-GCM with 128 bit ICV for both encryption and integrity.
- ike_proposals: You can modify the IKE (Main Mode) encryption and integrity algorithms, and the Diffie-Hellman group. The default, aes128-sha256-modp2048!, is 128 bit AES-CBC for encryption, SHA2_256_128 HMAC for integrity, and Group 14 for Diffie-Hellman.

Note: To modify the configuration in an existing deployment, you must update the manifest file and redeploy.

Download and Deploy the IPsec Add-on

After deploying Ops Manager, perform the following steps to download and deploy the IPsec add-on:

- 1. Download the IPsec add-on software binary from the Pivotal Network 🗵 to your local machine.
- 2. Copy the software binary to your Ops Manager instance.

 $\$ \ scp -i \ PATH/TO/PRIVATE/KEY \ ipsec-release.tar.gz \ ubuntu@YOUR-OPS-MANAGER-VM-IP: \\$

3. Copy the IPsec manifest file to your Ops Manager instance.

\$ scp -i PATH/TO/PRIVATE/KEY ipsec-addon.yml ubuntu@YOUR-OPS-MANAGER-VM-IP:

4. SSH into Ops Manager.

\$ ssh -i PATH-TO-PRIVATE-KEY ubuntu@YOUR-OPS-MANAGER-VM-IP

5. On the Ops Manager VM, navigate to the software binary location in your working directory.

\$ cd PATH-TO-BINARY

- 6. Log in to the BOSH Director.
 - For Ops Manager v1.10 or earlier:
 - i. On the Ops Manager VM, target the internal IP address of your BOSH Director. When prompted, enter your BOSH Director credentials. To retrieve your BOSH Director credentials, navigate to Ops Manager, click the **Credentials** tab, and click **Link to Credential** next to **Director Credentials**. For example:

- For Ops Manager v1.11 or later:
 - $i. \ \ On the Ops Manager VM, create an alias in the BOSH CLI for your Ops Manager Director IP address. For example: \\$

\$ bosh2 alias-env my-env -e 10.0.0.3

ii. Log in to the BOSH Director, specifying the newly created alias. For example:

\$ bosh2 -e my-env log-in

- 7. Upload your release, specifying the path to the tarballed IPsec binary, by running one of the following commands:
 - o For Ops Manager v1.10 or earlier:

\$ bosh upload release PATH-TO-BINARY/BINARY-NAME.tar

o For Ops Manager v1.11 or later:



\$ bosh2 -e my-env upload-release PATH-TO-BINARY/BINARY-NAME.tar

- 8. List the releases by running one of the following commands, and confirm that the IPsec binary file appears:
 - For Ops Manager v1.10 or earlier:

\$ bosh releases

o For Ops Manager v1.11 or later:

\$ bosh2 -e my-env releases

- 9. Update your runtime configuration to include the IPsec add-on.
 - For Ops Manager v1.10 or earlier:

\$ bosh update runtime-config PATH/bosh-manifest.yml

For Ops Manager v1.11 or later:

\$ bosh2 -e my-env update-runtime-config PATH/bosh-manifest.yml

- 10. Verify your runtime configuration changes match what you specified in the IPsec manifest file.
 - o For Ops Manager v1.10 or earlier:

\$ bosh runtime-config

o For Ops Manager v1.11 or later:

\$ bosh2 -e my-env runtime-config

For example,

```
S bosh2 -e my-env runtime-config
Acting as user 'admin' on 'micro'

releases:
- {name: ipsec, version: 1.0.0}

addons:
name: ipsec-addon
jobs:
- name: ipsec
release: ipsec
...
```

- 11. If you have not installed the Elastic Runtime tile, follow these steps:
 - a. Navigate to your ${\bf Installation}~{\bf Dashboard}$ in Ops Manager.
 - b. Click Apply Changes
 - c. Deploy Elastic Runtime by following the installation instructions for your laas. See the Installing Pivotal Cloud Foundry topic for more information.
- 12. If you have already deployed Elastic Runtime and are adding IPsec to an existing deployment, follow these steps:
 - a. Set the optional flag to true .
 - b. Navigate to your **Installation Dashboard** in Ops Manager.
 - c. Click Apply Changes
 - $\ d.\ Wait for the installation to complete.$
 - e. Set the optional flag to false .
 - f. Update the runtime config.
 - For Ops Manager v1.10 or earlier:

\$ bosh update runtime-config PATH/bosh-manifest.yml

■ For Ops Manager v1.11 or later:



\$ bosh2 -e my-env update-runtime-config PATH/bosh-manifest.yml

- g. Navigate to your Installation Dashboard.
- h. Click Apply Changes.
- 13. Secure the sensitive information in the ipsec-addon.yml file. Pivotal recommends encrypting the file and moving it to a secure location.

Verify Your IPsec Installation

After installing IPsec and deploying Elastic Runtime, perform the following steps to verify your IPsec installation:

- 1. List the job VMs in your deployment by running one of the following commands:
 - For Ops Manager v1.10 or earlier:

```
bosh vms
```

For Ops Manager v1.11 or later:

```
bosh2 -e BOSH_ENVIRONMENT vms
```

- 2. Open an SSH connection into the VM, using the job name and index of any VM found above, by running one of the following commands:
 - o For Ops Manager v1.10 or earlier:

```
bosh ssh JOB-NAME/INDEX
```

• For Ops Manager v1.11 or later: bosh2 -e BOSH_ENVIRONMENT -d DEPLOYMENT_NAME ssh JOB-NAME/INDEX

Note: The exact VM does not matter, because installing the IPsec add-on loads IPsec on all VMs deployed by Ops Manager.

- 3. Run sudo su to enter the root environment with root privileges.
- 4. Run monit summary to confirm that your ipsec job is listed as a bosh job.

```
The Monit daemon 5.2.5 uptime: 18h 32m
...
Process 'ipsec' running
System 'system_localhost' running
```

5. Run PATH-TO-IPSEC/ipsec statusall to confirm that IPsec is running. If IPsec is not running, this command produces no output.

```
$ /var/vcap/packages/strongswan-5.3.5/sbin/ipsec statusall
Status of IKE charon daemon (strongSwan 5.3.5, Linux 3.19.0-56-generic, x86_64):
malloc: sbrk 2314240, mmap 0, used 1182400, free 1131840
worker threads: 11 of 16 idle, 5/0/0/0 working, job queue: 0/0/0/0, scheduled: 206
loaded plugins: charon aes sha1 sha2 random nonce x509 revocation constraints pubkey pkcs1 pkcs7 pkcs8 pkcs12 pem gmp xcbc cmac hmac attr kernel-netlink socket-default stroke
Listening IP addresses:
10.10.5.66
Connections
ipsec-10.10.4.0/24: %any...%any IKEv1/2
ipsec-10.10.4.0/24: local: [CN=test-cert-1-ca-1] uses public key authentication
ipsec-10.10.4.0/24: cert: "CN=test-cert-1-ca-1"
ipsec-10.10.4.0/24: remote: uses public key authentication
ipsec-10.10.9.0/24: child: 10.10.5.66/32 === 10.10.9.0/24 TRANSPORT
no-ipsec-10.10.4.1/32: %any...%any IKEv1/2
no-ipsec-10.10.4.1/32: local: uses public key authentication
no-ipsec-10.10.4.1/32: remote: uses public key authentication
no-ipsec-10.10.4.1/32: child: dynamic === 10.10.4.1/32 PASS
Shunted Connections
no-ipsec-10.10.4.1/32: dynamic === 10.10.4.1/32 PASS no-ipsec-10.10.5.1/32: dynamic === 10.10.5.1/32 PASS
no\text{-ipsec-}10.10.6.1/32;\ dynamic === 10.10.6.1/32\ PASS
Routed Connections:
ipsec-10.10.9.0/24{6}: ROUTED, TRANSPORT, reqid 6
ipsec-10.10.9.0/24\{6\}: 10.10.5.66/32 === 10.10.9.0/24
ipsec-10.10.8.0/24{5}: ROUTED, TRANSPORT, reqid 5
ipsec\text{-}10.10.4.0/24\{1\}; \quad 10.10.5.66/32 === 10.10.4.0/24
Security Associations (45 up, 0 connecting):
ipsec-10.10.4.0/24[459]: ESTABLISHED 13 seconds ago, 10.10.5.66[CN=test-cert-1-ca-1]...10.10.4.38[CN=test-cert-1-ca-1]
ipsec-10.10.4.0/24{1527}: 10.10.5.66/32 === 10.10.4.38/32
```



Generate a Self-Signed Certificate

Note: Use a self-signed certificate only for development or test environments. Do not use a self-signed certificate for a production deployment. The scripts below generate private keys in a certs subdirectory.

To generate a self-signed certificate for your IPsec manifest, you can use either opensal or certstrap. Follow the instructions for your preferred method below.

Rerunning the scripts overwrites your current keys and the certificates.

Generate a Self-Signed Certificate with OpenSSL

- 1. Download M the openssl-create-ipsec-certs.sh bash script.
- 2. Navigate to the directory where you downloaded the script:

\$ cd ~/workspace

3. Change the permissions of the script:

\$ chmod u+x openssl-create-ipsec-certs.sh

4. Run the script:

\$./openssl-create-ipsec-certs.sh

5. Because this certificate expires in 365 days, set a calendar reminder to rotate the certificate within the year. For instructions on changing certificates, see Rotating IPsec Certificates.

Generate a Self-Signed Certificate with Certstrap

- 1. Download and install Go ☑.
- 2. Download I the certstrap bash script.
- 3. Navigate to the directory where you downloaded the script:

\$ cd ~/workspace

4. Change the permissions of the script:

\$ chmod u+x certstrap-create-ipsec-certs.sh

5. Run the script:

\$./certstrap-create-ipsec-certs.sh



Upgrading the IPsec Add-on for PCF

Page last updated:

This topic describes how to upgrade the IPsec add-on.

Upgrading the IPsec Add-On

- 1. Retrieve the latest runtime config by running one of the following commands:
 - For Ops Manager v1.10 or earlier: bosh runtime-config > PATH_TO_SAVE_THE_RUNTIME_CONFIG
 - For Ops Manager v1.11 or later: bosh2 -e BOSH_ENVIRONMENT runtime-config > PATH_TO_SAVE_THE_RUNTIME_CONFIG
- 2. Change the release version.

```
releases:
- {name: ipsec, version: NEW_VERSION}
```

- 3. Update the runtime config by running one of the following commands:
 - For Ops Manager v1.10 or earlier: bosh update runtime-config PATH_TO_SAVE_THE_RUNTIME_CONFIG
 - For Ops Manager v1.11 or later: bosh2 -e BOSH_ENVIRONMENT update-runtime-config PATH_TO_SAVE_THE_RUNTIME_CONFIG
- 4. Upload your new release.

\$ bosh upload release PATH-TO-BINARY/BINARY-NAME.tar

- 5. Navigate to your Installation Dashboard in Ops Manager.
- 6. Click Apply Changes.



Uninstalling the IPsec Add-on for PCF

Page last updated:

This topic describes how to uninstall IPsec from your deployment.

Uninstall the IPsec Add-On

- ${\bf 1.} \ \ {\bf Retrieve\ the\ latest\ runtime\ config\ by\ running\ one\ of\ the\ following\ commands:}$
 - For Ops Manager v1.10 or earlier: bosh runtime-config > PATH_TO_SAVE_THE_RUNTIME_CONFIG
 - For Ops Manager v1.11 or later: bosh2 -e BOSH_ENVIRONMENT runtime-config > PATH_TO_SAVE_THE_RUNTIME_CONFIG
- 2. Set the optional flag to true under IPsec properties.
- 3. Update the runtime config by running one of the following commands:
 - For Ops Manager v1.10 or earlier: bosh update runtime-config PATH/YOUR-RUNTIME-CONFIG.yml
 - For Ops Manager v1.11 or later: bosh2 -e BOSH_ENVIRONMENT update-runtime-config PATH_TO_SAVE_THE_RUNTIME_CONFIG
- 4. Navigate to your **Installation Dashboard** in Ops Manager.
- 5. Click Apply Changes.
- 6. Wait for the installation to complete.
- 7. Remove IPsec from the runtime config.
- 8. Update the runtime config by running one of the following commands:
 - For Ops Manager v1.10 or earlier: bosh update runtime-config PATH/YOUR-RUNTIME-CONFIG.yml
 - For Ops Manager v1.11 or later: bosh2 -e BOSH_ENVIRONMENT update-runtime-config PATH_TO_SAVE_THE_RUNTIME_CONFIG
- 9. Navigate to your **Installation Dashboard** in Ops Manager.
- 10. Click Apply Changes.

Checking Certificate Dates

Page last updated:

This topic describes how to check the expiration dates of IPsec certificates.

The following procedure describes how to download the runtime configuration file and extract the two IPsec certificates into temporary files. Then, the files are input to the OpenSSL tool. The OpenSSL tool decodes the certificates and displays the expiration dates.

Check Certificate Dates

Follow the steps below to determine the expiration dates of your IPsec certificates.

- 1. Log in to BOSH Director.
- 2. Run one of the following commands to download your runtime configuration YAML file:
 - For Ops Manager v1.10 or earlier: bosh runtime-config > PATH_TO_SAVE_THE_RUNTIME_CONFIG
 - For Ops Manager v1.11 or later: bosh2 -e BOSH_ENVIRONMENT runtime-config > PATH_TO_SAVE_THE_RUNTIME_CONFIG

For example,

```
bosh 2\ runtime-config > /tmp/my-runtime-config.yml
```

3. Display the runtime configuration YAML file so that you can copy from it. For example,

```
$ cat /tmp/my-runtime-config.yml
```

4. Identify the section of the file that contains IPsec properties, and locate the certificates:

```
addons:
- include:
 stemcell:
 - os: ubuntu-trusty
jobs:
- name: ipsec
 release: ipsec
name: ipsec
properties:
 ipsec:
  ca_certificates:
   MIIE/TCCAuWgAwIBAgIBATANBgkqhkiG9w0BAQsFADAOMQwwCgYDVQQDEwNjYTEw
   Axu2pbEoT1PrMd3HlAZ3AH8ZrMR3ScJKCW3wQFRX/Plj
    ---END CERTIFICATE
  instance_certificate:
    ----BEGIN CERTIFICATE--
   MIIEGTCCAgGgAwIBAgIQDlqK1V54BEknnblVPXu5lzANBgkqhkiG9w0BAQsFADAO\\
   MQwwCgYDVQQDEwNjYTEwHhcNMTYwNTI2MjI1MTAzWhcNMTgwNTI2MjI1MTAzWjAQ\\
   MQ4wDAYDVQQDEwVjZXJ0MTCCASIwDQYJKoZIhvcNAQEBBQADggEPADCCAQoCggEB
   4Q6P/cDn9QvW2QbbWkApP2uuMk04jWJV7p79CfX4pipPqiSofjFyFqsjjvir
   ----END CERTIFICATE--
```

5. Copy the ca_certificate into a text file. Retain the header and footer, but delete the leading white space before the -----BEGIN CERTIFICATE----- and ----END CERTIFICATE----- lines.

For example,

```
-----BEGIN CERTIFICATE-----
MIIE/TCCAuWgAwIBAgIBATANBgkqhkiG9w0BAQsFADAOMQwwCgYDVQQDEwNjYTEw
HhcNMTYwNTI2MjIIMDMzWhcNMjYwNTI2MjIIMDQyWjAOMQwwCgYDVQQDEwNjYTEw
...
Axu2pbEoT1PrMd3HIAZ3AH8ZrMR3ScJKCW3wQFRX/Plj
-----END CERTIFICATE-----
```

Pivotal

- 6. Save the file with the PEM extension, for example, my-ipsec-ca-cert.pem.
- 7. Run the following command:

openssl x509 -text -inform pem -in /PATH/FILENAME.pem | grep "Not After"

For example,

\$ openssl x509 -text -inform pem -in /tmp/my-ipsec-ca-cert.pem | grep "Not After" Not After : May 26 22:50:42 2026 GMT

If the PEM file is correctly formatted, the output shows a line with the $\frac{Not\ After}{}$ date. If the PEM file is not correctly formatted, The output shows $\frac{}{}$ unable to load certificate $\frac{}{}$.

- 8. Repeat steps 5–7 for the instance_certificate.
- Review the Not After date and plan to replace the certificates accordingly.
 Keep in mind the lead time to obtain new certificates and the time to perform a deployment to apply them.
 For information about rotating certificates, see About the Procedures above.
- 10. For security hygiene, delete three temporary files that you created: the downloaded copy of the runtime-config.yml which contains the private key and the two PEM files that contain the certificates.



Troubleshooting the IPsec Add-on for PCF

Page last updated:

This topic provides instructions to verify that strongSwan-based IPsec works with your Pivotal Cloud Foundry (PCF) deployment and general recommendations for troubleshooting IPsec.

Verify that IPsec Works with PCF

To verify that IPsec works between two hosts, you can check that traffic is encrypted in the deployment with tepdump, perform the ping test, and check the logs with the steps below.

- 1. Check traffic encryption and perform the ping test. Select two hosts in your deployment with IPsec enabled and note their IP addresses. These are referenced below as IP-ADDRESS-1 and IP-ADDRESS-2.
 - a. SSH into IP-ADDRESS-1.

\$ ssh IP-ADDRESS-1

b. On the first host, run the following, and allow it to continue running

\$ tcpdump host IP-ADDRESS-2

c. From a separate command line, run the following:

\$ ssh IP-ADDRESS-2

d. On the second host, run the following:

\$ ping IP-ADDRESS-1

e. Verify that the packet type is ESP. If the traffic shows ESP as the packet type, traffic is successfully encrypted. The output from topdump will look similar to the following:

- 2. Open the var/log/daemon.log file to obtain a detailed report, including information pertaining to the type of certificates you use, and to verify an established connection exists.
- 3. Navigate to your Installation Dashboard, and click **Recent Install Logs** to view information regarding your most recent deployment. Search for "ipsec" and the status of the IPsec job.
- 4. Run | ipsec statusall | to return a detailed status report regarding your connections. The typical path for this binary:

 | var/vcap/packages/strongswan-x.x.x/sbin | x.x.x | represents the version of strongSwan packaged into the IPsec.

If you experience symptoms that IPsec does not establish a secure connection, return to the <u>Installing the IPsec Add-on for PCF</u> topic and review your installation.

If you encounter issues with installing IPsec, refer to the Troubleshooting IPsec section of this topic.

Troubleshoot IPsec

IPsec Installation Issues

Symptom

 $Unresponsive\ applications\ or\ incomplete\ responses,\ particularly\ for\ large\ payloads$



Explanation: Packet Loss

IPsec packet encryption increases the size of packet payloads on host VMs. If the size of the larger packets exceeds the maximum transmission unit (MTU) size of the host VM, packet loss may occur when the VM forwards those packets.

If your VMs were created with an Amazon PV stemcell, the default MTU value is 1500 for both host VMs and the application containers. If your VMs were created with Amazon HVM stemcells, the default MTU value is 9001. Garden containers default to 1500 MTU.

Solution

Implement a 100 MTU difference between host VM and the contained application container, using one of the following approaches:

- Decrease the MTU of the application containers to a value lower than the MTU of the VM for that container. In the Elastic Runtime tile configuration, click Networking and modify Applications Network Maximum Transmission Unit (MTU) (in bytes) before you deploy. Decrease it from the default value of 1454 to 1354.
- Increase the MTU of the application container VMs to a value greater than 1500. Pivotal recommends a headroom of 100. Run ifconfig NETWORK-INTERFACE mtu MTU-VALUE to make this change. Replace NETWORK-INTERFACE with the network interface used to communicate with other VMs For example: \$ ifconfig NETWORK-INTERFACE mtu 1600

Symptom

Unresponsive applications or incomplete responses, particularly for large payloads

Explanation: Network Degradation

IPsec data encryption increases the size of packet payloads. If the number of requests and the size of your files are large, the network may degrade.

Solution

Scale your deployment by allocating more processing power to your VM CPU or GPUs, which, additionally, decreases the packet encryption time. One way to increase network performance is to compress the data prior to encryption. This approach increases performance by reducing the amount of data transferred.

IPsec Upgrade Issues

Symptom

Ops Manager returns an error when you click Apply Changes to Upgrade the PCF IPsec Add-On.

Explanation: Consul cluster failure

When BOSH applies the IPsec Add-on the VMs in the Consul cluster, the VMs cannot communicate with each other, which causes the cluster to fail. This can result in many different errors. For instance, you might see an error in Ops Manager that says a Diego cell is failing. In this case, it is likely that the Diego cell is failing because Consul is not running.

Solution

- 1. Scale down the number of Consul instances in Elastic Runtime to 1. For more information, see Scaling Elastic Runtime 🖫.
- 2. Click Apply Changes.
- 3. After the install succeeds, scale up the number of Consul instances to the previous value.



IPsec Runtime Issues

Symptom

Errors relating to IPsec, including symptoms of network partition. You may receive an error indicating that IPsec has stopped working.

For example, this error shows a symptom of IPsec failure, a failed clock global-partition:

Failed updating job clock_global-partition-abf4378108ba40fd9a43 > clock_global-partition-abf4378108ba40fd9a43/0
(ddb1fbfa-71b1-4114-a82c-fd75867d54fc)
(canary): Action Failed
get_task: Task 044424f7-c5f2-4382-5d81-57bacefbc238
result: Stopping Monitored Services: Stopping service
ipsec: Sending stop request to Monit: Request failed,
response: Response{ StatusCode: 503, Status: '503 Service Unavailable' } (00:05:22)..

Explanation: Asynchronous monit Job Priorities

When a monit stop command is issued to the NFS mounter job, it hangs, preventing a shutdown of the PCF cluster.

This is not a problem with the IPsec add-on release itself. Rather, it is a known issue with the NFS mounter job and the monit stop script that can manifest itself after IPsec is deployed with PCF v1.7.

This issue occurs when monit job priorities are asynchronous. Because the order of job shutdown is arbitrary, it is possible that the IPsec job will be stopped first. After this happens, the network connectivity for that VM goes away, and the NFS mounter job loses visibility to the associated storage. This causes the NFS mounter job to hang, and it blocks the monit stop from completing. See the Monit job Github details () for further information.

Note: This issue affects deployments using CF v231 or earlier, but in CF v232 the release uses an nginx blobstore instead of the NFS blobstore. The error does not exist for PCF deployments using CF releases greater than CF v231. The error also does not apply to PCF deployments that use WebDAV as their Cloud Controller blobstore.

Solution

- 1. BOSH ssh into the stuck instance by running one of the following commands:
 - $\circ~$ For Ops Manager v1.10 or earlier:

```
bosh ssh VM_INDEX
```

- For Ops Manager v1.11 or later: bosh2 -e BOSH_ENVIRONMENT -d DEPLOYMENT_NAME ssh VM_INDEX
- 2. Authenticate as root and use the sv stop agent command to kill the BOSH Agent:

```
$ sudo su
# sv stop agent
```

- 3. Run the following command to detect the missing monit job VM.
 - For Ops Manager v1.10 or earlier:

```
bosh cloudcheck
```

• For Ops Manager v1.11 or later: bosh2 -e ENVIRONMENT_NAME -d DEPLOYMENT_NAME cloud-check

For example,

```
# bosh cloudcheck
VM with cloud ID `vm-3e37133c-bc33-450e-98b1-f86d5b63502a' missing:

- Ignore problem
- Recreate VM using last known apply spec
- Delete VM reference (DANGEROUS!)
```

- 4. Choose Recreate VM using last known apply spec.
- 5. Continue with your deploy procedure.



Symptom

• App fails to start with the following message:

```
FAILED
Server error,
status code: 500,
error code: 10001,
message: An unknown error occurred.
```

The Cloud Controller log shows it is unable to communicate with Diego due to getaddrinfo failing.

• Deployment fails with a similar error message: diego_database-partition-620982d595434269a96a/0 (a643c6c0-bc43-411b-b011-58f49fb61a6f) is not running after update. Review logs for failed jobs: etcd

Explanation: Split Brain consul

This error indicates a "split brain" issue with Consul.

Solution

Confirm this diagnosis by checking the peers.json file from /var/vcap/store/consul_agent/raft. If it is null, then there may be a split brain. To fix this problem, follow these steps:

- 1. Run monit stop on all Consul servers:
- 2. Run rm -rf /var/vcap/store/consul_agent/ on all Consul servers.
- 3. Run monit start consul_agent on all Consul servers one at a time.
- 4. Restart the consul_agent process on the Cloud Controller VM. You may need to restart consul_agent on other VMs, as well.

Symptom

You see that communication is not encrypted between two VMs.

Explanation: Error in Network Configuration

The IPsec BOSH job is not running on either VM. This problem could happen if both IPsec jobs crash, both IPsec jobs fail to start, or the subnet configuration is incorrect. There is a momentary gap between the time when an instance is created and when BOSH sets up IPsec. During this time, data can be sent unencrypted. This length of time depends on the instance type, IAAS, and other factors. For example, on a t2.micro on AWS, the time from networking start to IPsec connection was measured at 95.45 seconds.

Solution

Set up a networking restriction on host VMs to only allow IPsec protocol and block the normal TCP/UDP traffic. For example, in AWS, configure a network security group with the minimal networking setting as shown below and block all other TCP and UDP ports.

Additional AWS Configuration

Туре	Protocol	Port Range	Source
Custom Protocol	AH (51)	All	10.0.0.0/16
Custom Protocol	ESP (50)	All	10.0.0.0/16
Custom UDP Rule	UDP	500	10.0.0.0/16

Note: When configuring a network security group, IPsec adds an additional layer to the original communication protocol. If a certain connection is targeting a port number, for example port 8080 with TCP, it actually uses IP protocol 50/51 instead. Due to this detail, traffic targeted at a blocked port may be able to go through.

Pivotal

Symptom

You see unencrypted app messages in the logs.

Explanation: etcd Split Brain

Solution

1. Check for split brain etcd by connecting with BOSH [ssh] into each etcd node:

\$ curl localhost:4001/v2/members

2. Check if the members are consistent on all of etcd. If a node has only itself as a member, it has formed its own cluster and developed "split brain." To fix this issue, SSH into the split brain VM and run the following commands:



b. # monit stop etcd

C. # rm -r /var/vcap/store/etcd

d. # monit start etcd

3. Check the logs to confirm the node rejoined the existing cluster.

Symptom

IPsec deployment fails with Error filling in template 'prestart.erb'

Error 100: Unable to render instance groups for deployment. Errors are:

- $-\ Unable\ to\ render\ jobs\ for\ instance\ group\ 'consul_server-partition-f9c4b18fd83cf3114d7f'.\ Errors\ are:$
- Unable to render templates for job 'ipsec'. Errors are:
- Error filling in template 'pre-start.erb' (line 12: undefined method `each_with_index' for #)
- $\ Unable \ to \ render \ jobs \ for \ instance \ group \ 'nats-partition-f9c4b18fd83cf3114d7f'. \ Errors \ are:$
- Unable to render templates for job 'ipsec'. Errors are:
- Error filling in template 'pre-start.erb' (line 12: undefined method `each_with_index' for #)

Explanation: Typographical or syntax error in deployment descritor YAML syntax

Solution

Check the deployment descriptor YAML syntax for the CA certificates entry:



```
- {name: ipsec, version: 1.0.0}
addons
  - name: ipsec-addon
            - name: ipsec
                 release: ipsec
         properties:
                             ipsec_subnets:
                             no_ipsec_subnets:
                                  - 10.0.1.10/32 # bosh director
                                instance_certificate: |
                                                           ---BEGIN CERTIFICATE--
                                       ----END CERTIFICATE----
                                instance_private_key:
                                              ----BEGIN EXAMPLE RSA PRIVATE KEY---
                                       MIIEogIBAAKCAQEAtAkBjrzr5x9g0aWgyDEmLd7m9u/ZzpK7UScfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANLaN7JiNz3cfANL
                                         ----END EXAMPLE RSA PRIVATE KEY----
                             ca_certificates:
                                       MIIEUDCCA rigAwIBAgIJAJVLBeJ9Wm3TMA0GCSqGSIb3DQEBCwUAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNVAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNVAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBgNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGzAZBGNAMB0xGZAZBGNAMB0xGZAZBGNAMB0xGNAMB0xGNAMB0xGNAMB0xGNAMB0xGNAMB0xGNAMB0xGNAMB0xGNAMB0xGNAMB0xGNAMB0xGNAMB0xGNAMB0xGNAMB0xGCNAMB0xGNAMB0xGNAMB0x
                                       BAMMEIBDRIBJUHNIYyBBZGRPbiBDQTAeFw0xNjA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVaFw0xOTA4MTUxNzQwNDVAFw0xOTA4MTUxNzQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw0xQwNDVAFw
                                            ----END CERTIFICATE----
```

In the example above, the values that appear after the ca_certificates: key are contained within a list and are not just a single certificate. This entry must be followed by a line starting with -, and ending with | . The lines following this contain the PEM encoded certificate(s).

The error message shown above indicating a problem with the each_with_index method provides a hint that the -| YAML syntax sequence is missing. Use this syntax even in situations where there is only one CA certificate, for example a list of one entry.

Symptom

Complete system outage with no warning.

Explanation: IPsec Certificates Might Have Expired

Expired IPsec certificates can cause a sudden system outage. For example, the self-signed certificates generated by the script provided in the installation instructions have a lifetime of 365 days. IPsec certificates expire if you do not rotate them within their lifetime.

Solution

Renew expired IPsec certificates. To avoid future downtime due to expired IPsec certificates, set a calendar reminder to rotate the certificates before they expire.

For how to renew certificates, see Renewing Expired IPsec Certificates. For how to rotate them, see Rotating IPsec Certificates.



Rotating Active IPsec Certificates

Page last updated:

This topic describes the process Pivotal recommends to increase deployment security by rotating certificates in the IPsec manifest.

Why You Need to Rotate Credentials

These are common reasons for rotating credentials:

- Your organizational security policy may specify how often you should apply these changes.
- Your certificates are going to expire. To find the expiration dates on your certificates, see Checking Certificate Dates.

About the Procedures

There are two procedures for certificate rotation described in this topic:

- The first procedure describes rotating the instance certificate and instance private key specified in your IPsec manifest, and requires updating BOSH. This procedure does not include rotating the certificate authority (CA) certificate.
- The second procedure describes rotating your CA certificate in addition to your instance certificate and instance private key. This procedure requires updating BOSH three times.

Note: The rolling deploys during these procedures result in minimal deployment downtime.

Procedure 1: Rotate the Instance Certificate and Instance Private Key

Follow the steps below to rotate the instance certificate and instance private key.

- 1. Generate a new certificate and use your existing IPsec CA certificate to sign the new certificate.
- 2. Update the instance certificate and the private key fields in your ipsec-addon.yml file with new values from the previous step.
- 3. Update the runtime config by running one of the following commands:
 - For Ops Manager v1.10 or earlier: bosh update runtime-config PATH_TO_SAVE_THE_RUNTIME_CONFIG
 - For Ops Manager v1.11 or later: bosh2 -e BOSH_ENVIRONMENT update-runtime-config PATH_TO_SAVE_THE_RUNTIME_CONFIG

Note: This step results in a few minutes of app downtime.

4. Navigate to your Ops Manager interface in a browser, and click **Apply Changes**.

Procedure 2: Rotate the CA Certificate, the Instance Certificate, and Instance Private Key

Follow these steps below to rotate the CA certificate, the instance certificate, and instance private key.

- 1. Generate a new CA certificate.
- 2. Append the newly generated CA certificate under the existing certificate as a new yaml list element in your ipsec-addon.yml . For example:

```
ca_certificates:
- |
    ----BEGIN CERTIFICATE----
...
----END CERTIFICATE----
- |
    ----BEGIN CERTIFICATE----
```



- 3. Update the runtime config by running one of the following commands:
 - For Ops Manager v1.10 or earlier: bosh update runtime-config PATH_TO_SAVE_THE_RUNTIME_CONFIG
 - o For Ops Manager v1.11 or later: bosh2 -e BOSH_ENVIRONMENT update-runtime-config PATH_TO_SAVE_THE_RUNTIME_CONFIG

Note: This step results in a few minutes of app downtime.

- 4. Navigate to your Ops Manager interface in a browser, and click **Apply Changes**.
- $5. \ \ Generate\ a\ new\ certificate\ and\ use\ your\ new\ IPsec\ CA\ certificate\ to\ sign\ the\ new\ certificate.$
- 6. Update the instance certificate and the private key fields in the YAML file with new values from above.
- 7. Repeat step 3 to update the runtime config.
- 8. Navigate to your Ops Manager interface in a browser, and click **Apply Changes**.
- 9. Delete the older CA certificate in the ipsec-addon.yml file.
- 10. Repeat step 3 to update the runtime config.
- 11. Navigate to your Ops Manager interface in a browser, and click **Apply Changes**.



Renewing Expired IPsec Certificates

Page last updated:

This topic describes the basic process that deployers may use to renew any soon-to-be-expiring certificates contained in the IPsec manifest.

About Certificate Expiration

The IPsec Add-on relies upon X.509 certificates to secure the communications between communicating peers.

Like all certificates, the IPsec certificates have a finite lifetime and eventually expire. The certificates generated by the procedure provided in the installation instructions, Generate a Self-Signed Certificate have a default lifetime of one year. Regardless of their specific lifetime, all certificates must eventually be rotated, and so it is important for the operations team to plan accordingly and remember to rotate the IPsec certificates before they actually expire.

IMPORTANT: Rotating the certificates while they are still valid ensures the maximum availability of the Cloud Foundry platform and avoids any unscheduled interruption in service.

Renew Expired IPsec Certificates

To renew expiring IPsec certificates, do the following:

- 1. Retrieve the latest runtime config by running one of the following commands:
 - For Ops Manager v1.10 or earlier: bosh runtime-config > PATH-TO-SAVE-THE-RUNTIME-CONFIG
 - o For Ops Manager v1.11 or later: bosh2 -e BOSH-ENVIRONMENT runtime-config > PATH-TO-SAVE-THE-RUNTIME-CONFIG
- 2. Generate a new set of certificates. For development or test environments, you can use self-signed certificates. For information about self-signed certificates, see Generate a Self-Signed Certificate.
- 3. In the runtime config.yml file saved from step 1, update the optional field to true and update the certificate fields with new certificates. For more information about these fields, see the field descriptions under Create the IPsec Manifest.

```
properties:
    ipsec:
    optional: true
    instance_certificate: |
        ----BEGIN CERTIFICATE----
    EXAMPLEAhigAwIBAgIRAIvrBy2TttU/LeRhO+Vlt0YwDQYJKoZIhvcNAQELBQAW
    ...
    ----END CERTIFICATE----
instance_private_key: |
        ----BEGIN EXAMPLE RSA PRIVATE KEY----
EXAMPLEXRSAXPRIVATEXKEYXDATAXEXAMPLEXRSAXPRIVATEXKEYXDATA
    ...
    ----END EXAMPLE RSA PRIVATE KEY----
ca_certificates:
    - |
        ----BEGIN CERTIFICATE-----
EXAMPLEAGAWIBAGIBATANBGkqhkiG9w0BAQsFADAUMRIwEAYDVQQDEwl0ZXN0
    ...
-----END CERTIFICATE-----
```

- ${\bf 4.} \ \ {\bf Update} \ the \ runtime \ config \ by \ running \ one \ of \ the \ following \ commands:$
 - For Ops Manager v1.10 or earlier: bosh update runtime-config PATH-TO-SAVE-THE-RUNTIME-CONFIG
 - o For Ops Manager v1.11 or later: bosh2 -e BOSH-ENVIRONMENT update-runtime-config PATH-TO-SAVE-THE-RUNTIME-CONFIG
- 5. Navigate to your Installation Dashboard in Ops Manager.
- 6. Click Apply Changes.
- 7. Remove the optional: true set in step 3.
- 8. Repeat steps 4 to 6.

Pivotal

Pivotal

Release Notes

Page last updated:

This topic contains release notes for the IPsec Add-on for PCF.

v1.6.15

Release Date: August 22, 2017



• Fixes a certificate validation issue on Linux VMs - Validate instance certificate is signed by one of the CA certificates

v1.6.14

Release Date: August 1, 2017

Note: If you have conflicts with the RabbitMQ HAProxy, check the Knowledgebase at support.pivotal.io

- Fixes the Optional flag for applying IPsec to an existing cluster
- Fixes log folder and files permissions (no impact to users)

v1.6.12

Release Date: July 28, 2017

Note: If you have conflicts with the RabbitMQ HAProxy, check the Knowledgebase at support.pivotal.io

- Restores syslog for logging
- IPsec log location is now configurable (default is syslog)
- Uses bosh stop instead of bosh drain

v1.6.9

Release Date: June 26, 2017

Note: This release does NOT write to Syslog; if you require Syslog, wait for the next patch release.

- Interim patch to avoid RabbitMQ Syslog timing conflict. If you don't have this timing conflict, you can ignore this patch.
- Update Strongswan to 5.5.3, fix USN-3301-1.
- Update golang to 1.8.1
- Update openssl to 1.0.2k
- Update openssl-fips to 2.0.14.
- Update gmp to 6.1.2.

v1.6.3



Release Date: March 10, 2017

- Supports Azure (for Linux VMs).
- Enables configuration of IKE and ESP proposals.
- Reduces downtime when applying IPsec to existing deployment through optional flag.
- Updates "xfrm_acq_expires" from 165 secs (default) to 6 secs to speed up retries.
- Fixes the ordering of IPsec and no-IPsec subnets.
- Uses aes128-sha256-modp2048! as the default IKE proposal.

Known Issues

- Spurious Configuration Warning: As part of the upgrade to StrongSwan version 5.4.0, this version of the IPsec add-on will emit a sequence of spurious configuration warning messages. The messages will appear similar to the following:
 - !! Your strongswan.conf contains manual plugin load options for charon.
 - !! This is recommended for experts only, see
 - !! http://wiki.strongswan.org/projects/strongswan/wiki/PluginLoad

These messages are both expected, and harmless. As a caution to end users, the StrongSwan software now emits a warning message when it detects that the installation includes a manually configured set of plug-ins. As a matter of security hygiene best practices, the IPsec add-on has always used a manual (explicit) configuration, and loads a restricted set of StrongSwan plug-ins. Any unused plug-ins are not loaded. The newest version of StrongSwan now issues this warning message when it detects that situation. The actual list of plug-ins in use has been determined to be appropriate for use of StrongSwan in the PCF environment. This warning is expected, and should be ignored.

• Certificate Verification: There is a known issue with the CA certificate validation. The IPsec add-on supports credential rotation with minimal downtime. The host instance certificate can be rotated at any time by doing a deployment. In addition, the CA certificate that is used to verify trust in the host certificates can be rotated with minimal downtime by doing multiple deployments.

However, because all VMs typically share the same instance certificate, they will trust each other without relying upon the CA certificate. The CA certificate is not actually needed until the operator does a deployment to rotate the instance certificate(s). While that deployment is running, some of the VMs will have received a new instance certificate, while other VMs are still operating using the prior instance certificate. During this time, while the instance certificates are different, the validation of the peer instance certificate will rely upon the common CA certificate in order to establish trust in the counterparty.

If the CA certificate is malformed, or otherwise invalid, this problem will remain latent until the time when the instance certificate is being rotated. It is only during that deployment when the operator will discover that the CA certificate is not valid. Of course, as long as the CA certificate is valid, there is no problem.

It is recommended that operators use a tool such as OpenSSL to verify that the CA certificate they are choosing to configure is in fact valid, and contains the appropriate details for proper end-entity authentication of the VM in the deployment (such as subjectName, issuerName, and validity dates, etc).

Operators can use their favorite certificate management tool to confirm that their certificate matches what they expect. Using OpenSSL, one can issue the command:

\$ openssl x509 -in myCA.crt -text

If this command produces valid output, then the certificate will be OK when configured for IPsec.

• MTU Sizing: Use 1354 on OpenStack. Keep the default on AWS and vSphere.